

OSC 92UL TEX-PLC Explosion proof PLC



<Features>

- Installing a PLC in explosion proof box to cope with various control in dangerous site.
- By means of LCD display and sheet key, possible to cope with operation at site.

<Specifications>

Model	TEX-PLC
DC input	24VDC 32 points 1 common
Relay output	24VDC/240VAC 16 points 1 common
Communication I/F	RS-232 x 1 ch
	RS422/485 x 1 ch
	CC-Link x 1 ch
Sheet key	24 points (6 x 4)

-Standard Internal Unit

CPU	Q00CPU
Input/output Composite Unit (for key board I/F)	QX48Y57
CC-Link Small Remote Input Unit	AJ65SBTB1-32D
CC-Link Small Remote Output Unit	AJ65SBTB2N-16R
CC-Link Unit	QJ61BT11
Serial communication Unit	Q61SP
Display	F943GOT-LWD

Internal unit can be manufactured in accordance with requirement.

<Optional extra>

- Dedicated key sheet
- 24 points (Vertical. 4 key x Horizontal. 6 keys)
- Can be produced in required key configuration
- Explosion proof CC-Link unit
- CC-Link unit only stored in explosion proof vessel.
- Possible I/O expansion in case number of input/output is short by TEX-PLC.