

OSC 92UL TL-300-LS/600-LS/1000-LS Low-pit type floor scale



<Specifications>

| Model | Capacity (kg) | Division (kg) | Working Surface(AxB) | Applicable to Nat'l assay | Material |
|------------|---------------|---------------|----------------------|---------------------------|--------------------------|
| TL-300-LS | 300 | 0.1 | 800 x 1,000 mm | YES | SUS304 (pickled surface) |
| | | | 1,200 x 1,200 mm | | |
| | | | 1,000 x 1,500 mm | | |
| TL-600-LS | 600 | 0.2 | 800 x 1,000 mm | NO | |
| | | | 1,200 x 1,200 mm | | |
| | | | 1,000 x 1,500 mm | | |
| TL-1000-LS | 1000 | 0.5 | 800 x 1,000 mm | NO | |
| | | | 1,200 x 1,200 mm | | |
| | | | 1,000 x 1,500 mm | | |

- Option
- * Both sides slope (standard one side slope)
 - * Checkered plate
 - * Iron made (SDS400 painted finished)

<Indicator specifications>

| Model | EDI-561 |
|------------------------|---|
| Protective performance | IP66 (excluding optional devices) |
| Weight display | Fluorescent tube, character size H32 x W14.6 mm |
| Dimensions | L14.5 x W290 x H198 mm |
| Power consumption | 15VA |
| Power source | 100VAC ±10-15% 50/60 Hz |
| Weight | approx. 4 kg |

- Option
- * Integrated journal printer
 - * Stand with casters
 - * RS232C in/output (cable 4 m)
 - * Relay contact in/output (cable 2 m)

